Please supply all a/w as High Resolution pdf

Zeus Reception Counter

- All artwork supplied must be PRINT READY, and will be printed as supplied.
- Please note PDF files will not be checked or amended by our Graphics Department.
- Artwork should be saved at 1/4 scale, CMYK, 300dpi, and with 3mm bleed.
- Please specify quantity required of each pdf supplied.

- We will email confirmation on receipt of your high res pdf artwork, but will NOT supply any proofs (unless requested).
- Where accurate colour matching is required you must supply pantone or printed references. We will match as closely as possible but cannot guarantee an exact match.



tech spec

Panel @ 25%: 495 x 220mm Full Size: 1980 x 880 APCON GRA



Reverse

Front

Artwork requirements

- Artwork must be set up at 25% with 3mm bleed in CMYK
- Images must not exceed 100% in size @ 300 dpi resolution
- Guidelines must not be within the artwork as these will print
- Colour profiles should not be embedded
- Overprint fill MUST be turned OFF in all cases
- All transparencies should be flattened



Indesign/Illustrator

• Export as PDF



- Settings:

 Adobe PDF Preset: [Press Quality]
- Bleed: 3mm

Please note: when using fonts with permission bits that do not allow embedding, a warning message will appear and the fonts will be substituted. You will therefore need to convert all text to outlines.



Quark

Export Layout as PDF

Settings:

- Bleed: Symmetric 3mm
- · Resolution: 300dpi



Acrobat Distiller

Settings

• Adobe PDF Preset: [Press Quality]



Graphics Department.

Clip Ltd. 210 Bristol Business Park, Athena The Close, Stoke Gifford, Bristol, BS16 1FJ

tel. +44 (0) 117 937 5700

fax. +44 (0) 117 9314561

5700 €

 ${\color{red}\mathsf{email.}} \quad in fo @clip display.com$

tp. C

www.clipdisplay.com call 0117 937 5700 for details

Sending Print Ready PDF Artwork.

All artwork sent through must be labelled with your company name, email address and order number.